SANITARY THERMOWELLS					
TYPE	MODEL WITH POLISHED BULB	DIMENSIONS connection T		EXTRA COSTS STAINLESS STEEL AISI316/1.4401	
	50 L	1" - DN25	rd 52x1/6		
СМ	20	1 1/2" - DN40	rd 65x1/6		
acc. to DIN 11851	Ls	2" - DN50	rd 78x1/6		
	(also available in SMS, RJT, IDF etc.)	3" - DN80	rd 104x1/6		
	50 L	1"	Ø 50.5		
тс	20	1 1/2"	Ø 50.5		
TRI CLAMP acc. to ISO 2852	Ls Ls	2"	Ø 64		
TV	60 20	DN50	Ø 50		
Varivent® In-Line	Ls D	Suitable for In Line housing DN25			
		DN68	Ø 68		
		Suitable for In Line housir	ng DN40 and up		

OPTIONS FOR BULB AND STEM						
OPTION	EXTRA COSTS					
OF HON	PER 100 MM					
BULB AND STEM AISI316/1.4401 for diameter 6, 8, 9, 10, 12, 13, 14, 15, 16, 18						
BULB AND STEM POLISHED (MECHANICAL) for all diameters						
BULB AND STEM PTFE® LINING (max.250°C)	MAXIMUM 1000 mm (longer: ON DEMAND)	first 100 mm:	O D			
BULB AND STEM HALAR® COATED (max.120°C)	MAXIMOM 1000 Hill (longer, ON DEMAND)	per 100 mm extra:	O D			