

TempStick Probe



TempStick Probe is a miniaturized temperature recorder with cable and rigid metal probe of various lengths, with a wide range of monitoring applications especially in the food, environment and pharmaceutical industry, for continuous monitoring in fridges and fridge cells according to ISO 9001 and 12830 standards, HACCP, FDA, BRC ecc. certification. Its reduced size and no need of external power supply make the TempStick system extremely versatile. The data logger can be supplied with calibration certificate with Accredia (Italian reference center, NIST equivalent) traceability.

The battery is User replaceable.

The rigid metal probe is made with stainless steel AISI 316L, food grade, and is available in different types:

- 3 cm length, 4 mm diameter, rounded tip for immersion (ordering code 03)
- 8 cm length, 4 mm diameter, rounded tip for immersion (ordering code 04)
- 3 cm length, 4 mm diameter, pointed tip for penetration (ordering code 05)
- 8 cm length, 4 mm diameter, pointed tip for penetration (ordering code 06)

Main features

- Mission programming and reading using a PC through the TecnoStick Interface or SRI and FLI portable interfaces
- Reduced size for easy use for every need
- Quick response time
- **Stand-by function:** start the logger and then, using the metallic clip, set it to a stand by status. In this way you can send many pre-programmed loggers to the sender of the products without providing him with the software and the interface. Before sending the goods he will just have to remove the clip to start the acquisitions
- Works with StickLog Pro, TS Manager and FridgeLog Z software

Plus

- High accuracy and precision
- Product's core temperature controlled directly
- Easy to use with SRI and FLI portable interfaces
- Compliant with HACCP and EN12830 regulations
- **MKT formula implemented**, for quick data analysis, also on SRI and FLI
- Provided with calibration certificate Accredia (NIST equivalent) traceable (on demand)
- Long life battery
- User replaceable battery



Applications



Food & Beverages



Environment



Cold Chain



Pharmaceutical



Healthcare



Laboratories



Medical



Warehouses



Logistic&Transport



Industrial

The system

The basic system, for transport, is made up by:

- TempStick data logger
- StickLog Pro software
- TecnoStick Interface or SRI

The FridgeLog Z system, for continuous monitoring, is made up by:

- TempStick data logger
- FridgeLog Z software
- FLI interface

It may be used for warehouses, environment, fridges validation:

- TempStick data logger
- TS Manager software
- TecnoStick Interface

Accessories

- TS Manager
- StickLog Pro
- FridgeLog Z
- TecnoStick Interface
- SRI
- FLI
- TempStick metal clip

Technical specifications

Dimensions	54 X 32 X 11 (mm)
Probe dimensions	Cable 300 l X 4 Ø (mm) or longer - Probe 30 or 80 l X 4 Ø (mm) pointed or rounded
Weight	14 g
Temperature range	-30 °C ÷ +60 °C
Sensor temperature range	-40 °C ÷ +80 °C
Standard calibration points (temperature)	-30/0/20/60°C
Extra calibration points (temperature)	Within the range -40 °C ÷ +80 °C
Temperature resolution	0,03 °C
Temperature accuracy	± 1 °C without certificate / ± 0,25 °C with Accredia traceable certificate (valid in the calibration range)
Memory (n. of acquisitions)	2.730
Acquisition step	From 1 every minute to 1 every 255 minutes
Battery type	3.0V CR2032 lithium, user replaceable (2017 IATA DGR: PI970 Section II, < 4 cells)
Battery life	Up to 10 years or 3 millions of acquisitions
Protection degree	IP63
Software&Mobile App	StickLog Pro, FridgeLog Z, TS Manager
Accessories	TecnoStick Interface, SRI, FLI



tecnosoft
WE DELIVER DATA

Tecnosoftware srl
Via Galvani, 4, 20068, Peschiera Borromeo (MI), Italy
T: (+39) 02 2692 2888 - F: (+39) 02 2692 2875
email: info@tecnosoft.eu - web: www.tecnosoft.eu
UNI EN ISO 9001:2008 Certiquality/IQNet N. 17733

